

NSW2010 Series gigabit Ethernet Switches

- NSW2010-5GT-POE-IN



- NSW2010-10GT-POE-IN



- NSW2010-18GT2GP-POE-IN



- NSW2010-26GT2GC-POE-IN



Key Features

- Support IEEE802.3 at standard, compatible with IEEE802.3 af by electrical equipment (PD)
- Supports PoE Power up to 30W for each PoE port;
- Auto detect power device; will not burned non-standard PoE device or normal PoE switch;
- Supports port power supply prioritization, guarantee the continuous power supply of key nodes;
- Supports IEEE802.3 x full duplex flow control and Backpressure half duplex flow control;
- Line-speed forwarding, intelligent identification
- Supports storage – and- forward for Data exchange;
- Support RJ45 Auto-MDI/MDIX

Specifications

Model	NSW2010-5GT-POE-IN	NSW2010-10GT-POE-IN	NSW2010-18GT2GP-POE-IN	NSW2010-26GT2GC-POE-IN
Ports	4×1000Mbps PoE ports (RJ45)+1×1000Mbps ports(RJ45)	8×1000Mbps PoE ports (RJ45)+2×1000Mbps ports(RJ45)	16×1000Mbps PoE ports (RJ45)+2×1000Mbps ports(RJ45)+2×1000Mbps ports (SFP)	24×1000Mbps PoE ports (RJ45)+2×1000Mbps ports(RJ45)+2×1000Mbps ports (Combo)
Standards	IEEE802.3,IEEE802.3u,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at		IEEE802.3,IEEE802.3u,IEEE802.3z,IEEE802.3ab,IEEE802.3x,IEEE802.3af,IEEE802.3at,IEEE802.3az	
Switching capacity	10Gbps	20Gbps	40Gbps	56Gbps
Forwarding performance	7.44Mpps	14.88Mpps	29.76Mpps	41.7Mpps
Packet Buffer	1M bit	2Mbit	4M bit	4Mbit
MAC	2K	2K	8K	8K
Dimensions (W×D×H)	140mm x 76.7mm x 27.7mm (5.5"×3"×1.1")	220mm x 150mm x 44mm (8.7"×5.9"×1.7")	280mm x 180mm x 44mm (11"×7.1"×1.7")	440mm x 207mm x 44mm (17.3"×8.1"×1.7")
Weight	<1kg	<1.24kg	<4.2kg	<5kg
Input Voltage	AC: 100-240V, 50/60Hz			
MAX. Power	65W	130W	200W	400W
PoE	802.3at/af, Mode A: 1/2+, 3/6-			
Max. PoE Power	Max capacity: 60W Max capacity for single port: 30W	Max capacity: 120W Max capacity for single port: 30W	Max capacity: 185W Max capacity for single port: 30W	Max capacity: 370W Max capacity for single port: 30W
Cooling Fans	0	1	1	2
Operating Temperature	0°C ~ 40 °C			
Storage Temperature	-40 °C ~ 70 °C			
Operating Humidity	10% ~ 90% non-condensing			
Storage Humidity	5% ~ 90% non-condensing			
Indicator	PWR(Green), LNK/ACT(Green), PoE(Orange)			
Working Mode	No	Default(Normal mode) : All ports can communicate with each other. VLAN(Secure mode): Downlink ports can communicate only with uplink ports. EXTEND(Surveillance mode): Transmission distance up to 250 meters. Downlink ports can communicate only with uplink ports.		

Zhejiang Uniview Technologies Co.,Ltd.

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2022 Zhejiang Uniview Technologies Co.,Ltd. All rights reserved.

* Product specifications and availability are subject to change without notice.